

ANEXO No 4

ARCHIVOS DE CONFIGURACION DE DESIGNER/2000

Archivos de configuración en el Servidor de Oracle

LISTENER.ORA

```

LISTENER =
  (ADDRESS_LIST =
    (ADDRESS=
      (PROTOCOL= IPC)
      (KEY= oracle.world)
    )
    (ADDRESS=
      (PROTOCOL= IPC)
      (KEY= ORCL)
    )
    (ADDRESS=
      (PROTOCOL= IPC)
      (KEY= EXTPROC0)
    )
    (ADDRESS=
      (COMMUNITY= NMP.world)
      (PROTOCOL= NMP)
      (SERVER= PREMIO3)
      (PIPE= ORAPIPE)
    )
    (ADDRESS=
      (PROTOCOL= TCP)
      (Host= premio3)
      (Port= 1521)
    )
    (ADDRESS=
      (PROTOCOL= TCP)
      (Host= premio3)
      (Port= 1526)
    )
    (ADDRESS=
      (PROTOCOL= TCP)
      (Host= 127.0.0.1)
      (Port= 1521)
    )
    (ADDRESS=
      (PROTOCOL= SPX)
      (Service= premio3_lsnr)
    )
  )
STARTUP_WAIT_TIME_LISTENER = 0
CONNECT_TIMEOUT_LISTENER = 10
TRACE_LEVEL_LISTENER = 0
SID_LIST_LISTENER =
  (SID_LIST =
    (SID_DESC =
      (GLOBAL_DBNAME = premio3)
      (SID_NAME = d703)
    )
    (SID_DESC =
      (SID_NAME = extproc)
      (PROGRAM=extproc)
    )
  )

```

```

)
)
PASSWORDS_LISTENER = (oracle)

```

TNSNAMES.ORA

```

Beq-local.world =
  (DESCRIPTION =
    (ADDRESS_LIST =
      (ADDRESS =
        (PROTOCOL = BEQ)
        (PROGRAM = oracle80)
        (ARGV0 = oracle80ORCL)
        (ARGS = ' (DESCRIPTION=(LOCAL=YES) (ADDRESS=(PROTOCOL=beq) ) ) ')
      )
    )
    (CONNECT_DATA = (SID = d703)
  )
)
Tcp-loopback.world =
  (DESCRIPTION =
    (ADDRESS_LIST =
      (ADDRESS =
        (PROTOCOL = TCP)
        (Host = 127.0.0.1)
        (Port = 1521)
      )
    )
    (CONNECT_DATA = (SID = d703)
  )
)
tesis.world =
  (DESCRIPTION =
    (ADDRESS_LIST =
      (ADDRESS =
        (PROTOCOL = TCP)
        (Host = premio3)
        (Port = 1521)
      )
    )
    (CONNECT_DATA = (SID = d703)
  )
)
SpXExample.world =
  (DESCRIPTION =
    (ADDRESS_LIST =
      (ADDRESS =
        (PROTOCOL = SPX)
        (Service = Server_lsnr)
      )
    )
    (CONNECT_DATA = (SID = ORCL)
  )
)

```

```

)
NmpExample.world =
  (DESCRIPTION =
    (ADDRESS_LIST =
      (ADDRESS =
        (PROTOCOL = NMP)
        (Server = FinanceServer1)
        (Pipe = ORAPIPE)
      )
    )
  (CONNECT_DATA = (SID = ORCL)
  )
)
CMEExample.world =
  (DESCRIPTION=(address_list=
    (ADDRESS=
      (PROTOCOL=tcp) (PORT=1610) (HOST=CM_SERVER))
    (ADDRESS=
      (PROTOCOL=tcp) (PORT=1521) (HOST=LSNR_SERVER)))
  (CONNECT_DATA=(SID=d703))
  (SOURCE_ROUTE=yes)
  )
extproc_connection_data.world =
  (DESCRIPTION =
    (ADDRESS =
      (PROTOCOL = IPC)
      (KEY = EXTPROC0)
    )
  (CONNECT_DATA = (SID = extproc)
  )
  )
)

```

SQLNET.ORA

```

TRACE_LEVEL_CLIENT = OFF
#sqlnet.authentication_services = (NONE)
names.directory_path = (TNSNAMES, HOSTNAME)
names.default_domain = world
name.default_zone = world
automatic_ipc = off

```

Archivos de configuración en el cliente de Oracle

TNSNAMES.ORA

```

# C:\ORAWIN95\NET80\ADMIN\TNSNAMES.ORA Configuration
File:C:\ORAWIN95\net80\admin\tnsnames.ora
# Generated by Oracle Net8 Assistant

```

```

CMEXAMPLE.WORLD =
  (DESCRIPTION =
    (ADDRESS_LIST =

```

```

        (ADDRESS = (PROTOCOL = tcp) (PORT = 1610) (HOST = CM_SERVER))
        (ADDRESS = (PROTOCOL = tcp) (PORT = 1521) (HOST = LSNR_SERVER))
    )
    (CONNECT_DATA = (SID = ORCL))
    (SOURCE_ROUTE = yes)
)

TCPEXAMPLE.WORLD =
    (DESCRIPTION =
        (ADDRESS = (PROTOCOL = TCP) (Host = Production1) (Port = 1521))
        (CONNECT_DATA = (SID = ORCL))
    )
)

NMPEXAMPLE.WORLD =
    (DESCRIPTION =
        (ADDRESS = (PROTOCOL = NMP) (Server = FinanceServer1) (Pipe = ORAPIPE))
        (CONNECT_DATA = (SID = ORCL))
    )
)

EXTPROC_CONNECTION_DATA.WORLD =
    (DESCRIPTION =
        (ADDRESS = (PROTOCOL = IPC) (KEY = EXTPROC0))
        (CONNECT_DATA = (SID = extproc))
    )
)

BEQ-LOCAL.WORLD =
    (DESCRIPTION =
        (ADDRESS = (PROTOCOL = BEQ) (PROGRAM = oracle80) (ARGV0 =
oracle80ORCL) (ARGS =
' (DESCRIPTION=(LOCAL=YES) (ADDRESS=(PROTOCOL=beq))) '))
        (CONNECT_DATA = (SID = ORCL))
    )
)

SPXEXAMPLE.WORLD =
    (DESCRIPTION =
        (ADDRESS = (PROTOCOL = SPX) (Service = Server_lsnr))
        (CONNECT_DATA = (SID = ORCL))
    )
)

TCP-LOOPBACK.WORLD =
    (DESCRIPTION =
        (ADDRESS = (PROTOCOL = TCP) (Host = 127.0.0.1) (Port = 1521))
        (CONNECT_DATA = (SID = ORCL))
    )
)

TESIS.WORLD =
    (DESCRIPTION =
        (ADDRESS = (PROTOCOL = TCP) (HOST = 190.1.1.37) (PORT = 1521))
        (CONNECT_DATA = (SID = d703))
    )
)

```

SQLNET.ORA

```
AUTOMATIC_IPC = OFF  
TRACE_LEVEL_CLIENT = OFF  
names.directory_path = (TNSNAMES)  
names.default_domain = world  
name.default_zone = world
```